


S-Band GaN/SiC, RF Power Amplifier Pallet

2.6-3.1 GHz | 2.6 kW | 53% Efficiency typ | 14 dB Gain typ | 100 V | 10 μ s Pulse Length, 1% Duty Cycle

IGNP2631M2600 is a high power GaN-on-SiC RF power amplifier pallet that has been designed to suit the unique needs of S-Band Systems. It operates over the full 2.6 - 3.1 GHz frequency range. Under 10 μ s, 1% duty cycle pulse conditions it supplies a minimum of 2.6 kW of peak output power, with typically >14 dB of associated gain and 53% efficiency. It operates from a 100 V supply voltage.



FEATURES

- GaN on SiC HEMT Technology
- Output Power >2600W
- Fully matched to 50 Ω
- High Efficiency
- 100% RF Tested Under 10 μ s, 1% duty cycle pulse conditions

APPLICATIONS

- S-Band Directed Energy systems
- S-Band Radar Systems

Table 1. RF Electrical Characteristics (Case temperature = 30 °C unless otherwise stated)

Parameter	Symbol	Min	Typ	Max	Units	Test Conditions
Gain	G	9	14	16	dB	$P_{OUT} = 2600W$ $f = 2.6, 2.85, 3.1 \text{ GHz}$ 10 μ s pulse length, 1% duty cycle $V_{DS} = 100V, I_{DS} = 200 \text{ mA}$
Drain Efficiency	η	45	53	65	%	
Pulse Droop	D	0	-0.5	-0.8	dB	
Load Mismatch Stability	VSWR-S	3:1				
Input Return Loss	IRL	7	12	20	dB	

Note: Consult Integra Technologies Application Note 001 for information on how RF output power and pulse droop are measured.

Table 2. Absolute Maximum Ratings (Not Simultaneous)

Parameter	Symbol	Value	Units	Test Conditions
DC Drain-Source Voltage	V_{DS}	300	V	25 °C
DC Gate-Source Voltage	V_{GS}	-8 to +1	V	25 °C
DC Drain Current per side	I_D	24	A	25 °C
DC Gate Current per side	I_G	4.8	mA	25 °C
RF Input Power	$P_{RF,IN}$	300	W	25 °C
Operating Channel Temperature	T_{CH}	-55 to +225	°C	
Storage Temperature	T_{STG}	-55 to +150	°C	
Soldering Temperature	T_{SOLDER}	260 for 60s	°C	

Note: Operation outside the limits given in this table may cause permanent damage to the transistor

Table 3. DC Electrical Characteristics (Case temperature = 25 °C unless otherwise stated)

Parameter	Symbol	Min	Typ	Max	Units	Test Conditions
Gate Pinch-Off Voltage per side	V_P	-5.0			V	$V_{DS} = 100V, I_{DS} = 1mA$
Quiescent Gate Voltage per side	V_Q		-4		V	$V_{DS} = 100V, I_{DS} = 100mA$

TYPICAL RF PERFORMANCE




Figure 1.




Figure 2.




Figure 3.

TYPICAL THERMAL PERFORMANCE

Table 4. Thermal Resistance (Case temperature = 85 °C unless otherwise stated)

Parameter	Symbol	Typ	Units	Test Conditions
Peak Thermal Resistance, Channel to Case per side	R_{TH}	0.12	°C/W	$P_{DISS} = 1152W$ per side 10 μs pulse length 1% duty cycle $V_{DS} = 100V$





Figure 4. (Data obtained by FEA analysis)

DIMENSIONS



ESD & MSL Rating

Parameter	Rating	Standard
ESD Human Body Model (HBM)	TBD	ESDA/JEDEC JS-001-2012
ESD Charged Device Model (CDM)	TBD	JEDEC JESD22-C101F
Moisture Sensitivity Level (MSL)	Unlimited Shelf Life	IPC/JEDEC J-STD-020

REACH Compliance

Integra Technologies supports EU Regulation number 1907/2006 concerning the Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) as these apply to Integra semiconductor products, development tools, and shipping packaging.

In support of the REACH regulation, Integra will:

- Inform customers and recipients of Integra product if they contain any substances that are of very high concern (SVHC) per the European Chemical Agency (ECHA) website.
- Notify ECHA if any Integra product that contains any SVHCs which exceed guidelines for REACH chemicals by weight per part number and for total content weight per year for all products produced in or imported to the European market.
- Cease shipments of product containing REACH Annex XIV substances until authorization has been obtained.
- Cease shipment of product containing REACH Annex XVII chemicals when restrictions apply.

Integra has evaluated its materials, BOMs, and product specifications and product and has determined that this transistor conforms to all REACH and SVHC regulations and guidelines. Integra has implemented actions and control programs that will assure continued compliance.

Disclaimer

Integra Technologies Inc. reserves the right to make changes without further notice to any products herein. Integra Technologies Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Integra Technologies Inc. assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Integra Technologies Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Integra Technologies Inc. customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Integra Technologies Inc. for any damages resulting from such improper use or sale.

DEFINITIONS:**DATA SHEET STATUS**

Advanced Specification - This data sheet contains Advanced specifications.

Preliminary Specification - This data sheet contains specifications based on preliminary measurements and data.

Final Specification - This data sheet contains final product specifications.

MAXIMUM RATINGS Stress above one or more of the maximum ratings may cause permanent damage to the device. These are maximum ratings only operation of the device at these or at any other conditions above those given in the characteristics sections of the specification is not implied. Exposure to maximum values for extended periods of time may affect device reliability.