

25 Watt ♦ 4 GHz ♦ GaN on SiC ♦ Packaged Transistor

- ♦ GaN HEMT Technology
- ♦ All Gold Metal System
- ♦ Broadband Unmatched Design
- ♦ Frequency of Operation: DC to 4GHz
- ♦ 28V Operation
- ♦ S-Parameter CAD Files Available Upon Request



Absolute Maximum Ratings


Parameter	Symbol	Rating	Units	Conditions
Drain Voltage	V_D	40	V	25°C
Gate Voltage	V_G	-50 to 0	V	25°C
Drain-Gate Voltage	V_{DG}	80	V	25°C
Drain Current	I_D	5.0	A	25°C
Gate Current	I_G	28	mA	25°C
Input CW Power	P_{IN}	37	dBm	25°C
Storage Temperature	T_{STG}	-55 to +150	°C	--
Channel Temperature	T_{CH}	200	°C	--

Parameters

Parameter	Symbol	Min	Typ	Max	Units	Conditions
Gate Threshold Voltage	$V_{GS(TH)}$	--	-3.6	--	V	$V_{DS} = 28\text{ V}, I_D = 500\text{ mA}$
Capacitance Gate-Source	C_{GS}	--	3.6	--	pF	$V_{DS} = 28\text{ V}, I_D = 500\text{ mA}$
Capacitance Gate-Drain	C_{GD}	--	0.12	--	pF	$V_{DS} = 28\text{ V}, I_D = 500\text{ mA}$
Capacitance Drain-Source	C_{DS}	--	0.6	--	pF	$V_{DS} = 28\text{ V}, I_D = 500\text{ mA}$
Gain	G	--	18	--	dB	Note 1
Power Output Saturated	P_{SAT}	--	44	--	dBm	Note 1
Power Added Efficiency	PAE	--	56	--	%	Note 1
Leak Rate	LR	--	--	1×10^{-3}	--	Rate per MIL-STD-750D, atm-cm ³ /sec
Thermal Resistance	θ_{JC}	--	--	4.0	°C/W	Note 1, $P_{OUT} = 44\text{ dBm}$

Note 1: $V_{DD}=28\text{V}, I_{DQ}=500\text{mA}, T_F=25^\circ\text{C}, F=3.0\text{GHz}$.

Package Outline Drawing



Definitions

Data Sheet Status	
Proposed Specification	This data sheet contains proposed specifications.
Preliminary Specification	This data sheet contains specifications based on preliminary measurements and data.
Product Specification	This data sheet contains final product specifications.
Maximum Ratings	
Stress above one or more of the maximum ratings may cause permanent damage to the device. These are maximum ratings only operation of the device at these or at any other conditions above those given in the characteristics sections of the specification is not implied. Exposure to maximum values for extended periods of time may affect device reliability.	

Disclaimer

Integra Technologies Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Integra Technologies Inc. assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Integra Technologies Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Integra Technologies Inc. customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Integra Technologies Inc. for any damages resulting from such improper use or sale.