


**L-Band Avionics Transistor**

- Silicon LDMOS Technology
- $P_{OUT-PK} = 950W$  @ ELM Mode S/6.4%/50V
- 1030MHz Operating Frequency
- Internal Impedance Pre-matched Device
- Specified For Use Under Class AB Operation
- Metal Based Package Sealed With Ceramic-Epoxy Lid
- Gold Metallization System: Chip - Wire Bond - Package
- Package Size: W=1.620" (41.15mm), L=0.400" (20.30mm)
- 100% High Power RF Tested in Broadband RF Test Fixture






PARAMETER	SYM	MIN	TYP	MAX	UNITS	TEST CONDITIONS
<b>DC ELECTRICAL SPECIFICATIONS</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	92	--	--	V	$I_{DS}=70mA, V_{GS}=0V, T_{F1}, S1$
Drain Leakage Current	$I_{DSS}$	--	--	48	$\mu A$	$V_{DS}=50V, V_{GS}=0V, T_{F1}, S1$
Operating Gate Voltage	$V_{GS}$	1.75	--	5.25	V	$V_{DS}=5V, I_D=100mA, T_{F1}, S1$
Gate Leakage Current	$I_{GSS}$	--	--	1	$\mu A$	$V_{GS}=5V, V_{DS}=0V, T_{F1}, S1$
<b>RF ELECTRICAL SPECIFICATIONS</b>						
Input Return Loss	IRL	-18	-12	-10	dB	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, $T_{F1}, S1$
Output Power	$P_o$	950	1100	1507	W	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, $T_{F1}, S1$
Power Gain	G	15.3	16.0	17.3	dB	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, $T_{F1}, S1$
Drain Efficiency	$N_D$	38	55	75	%	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, $T_{F1}, S1$
Pulse Amplitude Droop	D	-0.60	-0.50	+0.30	dB	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, $T_{F1}, S1$
Load Mismatch Stability	VSWR-S	2:1	--	--	--	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, $T_{F1}, S1$
Load Mismatch Tolerance	LMT	3:1	--	--	--	PIN1, V1, $I_{DQ1}$ , PW1, DF1, F1, $T_{F1}, S1$
<b>DC &amp; RF TEST CONDITIONS</b>						
Input Power 1	PIN1	--	28	--	W	--
Drain Supply Voltage 1	V1	--	50	--	V	--
Quiescent Drain Current 1	$I_{DQ1}$	--	60	--	mA	--
Pulse Format	PW1	--	*	--	--	*ELM mode S, 48 x (32 $\mu s$ ON, 18 $\mu s$ off), 6.4%
Duty Factor 1	DF1	--	6.4	--	%	--
Frequency 1	F1	--	1030	--	MHz	--
Flange Temperature 1	$T_{F1}$	20	25	30	$^{\circ}C$	--


PARAMETER	SYM	MIN	MAX	UNITS	SCREEN	CONDITIONS
<b>MAXIMUM RATINGS</b>						
Drain-Source Voltage	$V_{DS}$	--	92	V	BD	$T_F = 25^\circ\text{C}$
Gate-Source Voltage	$V_{GS}$	-10	12	V	BD	$T_F = 25^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55	+150	$^\circ\text{C}$	BD	--
Operating Junction Temperature	$T_J$	-55	+200	$^\circ\text{C}$	BD	--
<b>PROCESS SPECIFICATIONS</b>						
DC Wafer Probe	--	--	--	--	100%	Per Integra Spec
Wafer DC, RF Qualification	--	--	--	--	Q1	Per Integra Spec
Wire Bond Strength	--	--	--	--	LM	Per Integra Spec
Pre-cap Visual Inspection	--	--	--	--	100%	Per Integra Spec
Gross Leak Test – MIL-STD-750D	--	--	--	--	100%	Method 1071.6 C
<b>THERMAL RESISTANCE</b>						
Peak Thermal Resistance Per Rated RF Specification	$R_{TH(JC)}$	--	0.045	$^\circ\text{C/W}$	BD	$T_F = 25^\circ\text{C}$
<b>SCREENING LEVELS</b>						
Screening Level 1	S1	100	--	--	%	--
Parameter Qualified By Design	BD	--	--	--	--	--
Parameter Qualified By 3 Pieces (min) Per Wafer	Q1	--	--	--	--	--
Parameter Qualified By Assembly Line Monitor	LM	--	--	--	--	--

RF TEST FIXTURE – BROADBAND		
▶ Broadband RF Test Fixture. Provides Device Impedance Matching to 50Ω at the Rated Operating Frequency.		
▶ Electronic CAD Drawing File Available Upon Request. Includes Circuit Dimensions and Parts List.		
▶ Reference Design PCB: Rogers 3010 10.2, .025" 1oz. Cu, DK=10.2.		
FREQUENCY (MHz)	$Z_{IF}(\Omega)$	$Z_{OF}(\Omega)$
1030	$0.4 - j0$	$0.4 + j0.8$
Impedance Definition		

**TYPICAL PERFORMANCE**



PACKAGE OUTLINE DRAWING



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.615	1.625	41.02	41.27
B	1.395	1.405	35.43	35.69
C	0.634	0.674	16.10	17.12
D	0.395	0.405	10.03	10.29
E	1.219	1.241	30.96	31.52
F	0.455	0.465	11.56	11.81
G	0.075	0.085	1.90	2.16
H	0.120	0.130	3.05	3.30
J	0.535	0.545	13.59	13.84
K	0.059	0.069	1.499	1.753
L	0.081	0.091	2.06	2.31
M	0.164	0.194	4.16	4.93
N	0.004	0.007	0.10	0.18
Q	0.354	0.364	8.99	9.24

PIN SCHEDULE	
1	SOURCE
2	GATE
3	DRAIN

DEFINITIONS	
DATA SHEET STATUS	
Proposed Specification	This data sheet contains proposed specifications.
Preliminary Specification	This data sheet contains specifications based on preliminary measurements and data.
Product Specification	This data sheet contains final product specifications.
MAXIMUM RATINGS	
Stress above one or more of the maximum ratings may cause permanent damage to the device. These are maximum ratings only operation of the device at these or at any other conditions above those given in the characteristics sections of the specification is not implied. Exposure to maximum values for extended periods of time may affect device reliability.	

DISCLAIMER
Integra Technologies Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Integra Technologies Inc. assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Integra Technologies Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Integra Technologies Inc. customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Integra Technologies Inc. for any damages resulting from such improper use or sale.